



- GENERAL NOTES
1. ALL DIMENSIONS ARE IN INCHES OR FEET U.O.N.
 2. LADDERS SHALL BE AVAILABLE UPON REQUEST.
 3. CONCRETE SHALL BE GRADE N25.
 4. CONVERSION SLAB AND ADJUSTMENT SEGMENTS TO BE SUPPLIED SEPARATELY.
 5. CENTRE POINT OF ACCESS CHAMBER TO BE ON INTERSECTION POINT OF SEWERS.
 6. ONLY ACCESS CHAMBERS AND COMPONENTS APPROVED BY LOCAL AUTHORITY SHALL BE USED. THIS DRAWING IS AN EXAMPLE DRAWING. THE DETAILS OF SOME CHAMBERS MAY VARY FROM THOSE SHOWN IN THE DRAWING.
 7. PE WELDING TO BE CARRIED OUT BY ACCREDITED PERSONNEL ONLY (REFER TO MANUFACTURER FOR DETAILS).
 8. MANHOLE CAN BE ADJUSTED BY CUTTING CONVERSION TO REQUIRED HEIGHT USING STANDARD CUTTING EQUIPMENT.
 9. BASE, LINERS AND REDUCER COMPONENTS ROTOMOULDED FROM MDPE 0.6" WALL THICKNESS.
 10. ACCESS CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS INSTRUCTIONS.
 11. BACKFILL AND COMPACTION IN ACCORDANCE WITH LOCAL AUTHORITY INSTRUCTIONS OF WHERE THE PRODUCT IS TO BE INSTALLED.

A	03/08/2023	ORIGINAL ISSUE - US MARKET	MAS	DR	

QUICKSTREAM SOLUTIONS

This drawing is the property of Quickstream Solutions Inc. and shall not be copied without permission.

DO NOT SCALE FROM DRAWING

SCALE: DIAGRAMMATIC

DRAWN BY: MAS DATE: 03/08/2023

CHECKED BY: DR DATE: 03/08/2023

ALL DIMENSIONS ARE IN INCHES AND FEET

SMARTPIT CONFINED ACCESS CHAMBER

DRAWING REF: QS-SMARTPIT SHEET: 1 OF 1 ISSUE: C

ORIGINAL SHEET SIZE
A3